How to bridge your network

Pick a situation:

1. No cable connection available (Page 2)

What do you need:

- a. Active Wi-Fi connection
- b. Notebook with Ethernet port and Wi-Fi
- c. Lan cable
- 2. No cable or Wi-Fi available (Page 5)

What do you need:

- a. Android smartphone mobile internet
- b. Notebook with Ethernet port
- c. Lan cable
- d. Cable from smartphone to USB

No cable connection available.

- 1. Connect your notebook to an active Wi-Fi connection
- 2. Right click the internet icon and select "Open network & internet settings"



5. In the new windows select Network and sharing center

22		
🐼 Start	Status	
Instaling maken	Networkstatus	Hebt u een vraag?
Instanting content	INCLIVE INSTALLOS	Assistentie
Netwerk en internet		
🕮 Status	Ethernet 7	Maak Windows beter
	Openbaar netwerk	Feedback geven
Ethernet	U hebt verbinding met internet	
🕾 Inbelverbindingen	Als u een beperkt data-abonnement hebt, kunt u van dit netwerk een verbinding met een datalimiet maken of andere	
	eigenschappen wijzigen.	
- VPIN	Verbindingseigenschappen wijzigen	
🕸 Vliegtuigstand	Beschikbare netwerken weergeven	
₽ ● Mobiele hotspot	Netwerkinstellingen wijzigen	
() Dataverbruik	Adapteropties wijzigen	
@ Prov	Bekijk netwerkadapters en wijzig verbindingsinstellingen.	
	Bedgetes. Bergene soor di restaenken waarmee u verhinding maaki, wit u wilt oder.	
	Probleemoplossing voor netwerken Netwerkproblemen vaststellen en oplossen.	
	Netwerkeigenschappen weergeven	
	Netwerkcentrum	
	Network oppings instellen	
🔹 오 타 🖿 💼 💼 🧣	ເ 🔿 🗘 🕐	x ² ∧ 100 ⊂ ⇔ d ² 100 3-12-2018 🖣

4. On the left side you can pick " Change adapter settings"



5. Now you should see 2 connections. 1 is your current and active Wi-Fi connection. The other is your cable port. If you have multiple adapters and you are not sure which is your cable port. Insert a cable. The network adapter will change its status and now you know which adapter is your cable port. Unplug the cable after checking.



- 6. Now select both connections. And right click on your Wi-Fi connection.
- 7. Now choose "Bridge connections"



8. Windows now creates the network bridge.



9. When the bridge is created you can connect a LAN cable between the notebook and the CTouch screen. The notebook will now share it's Wi-Fi connection to the screen.



10. When you are done using the connection you can delete the bridge to restore normal functioning of the laptop.



No cable or Wi-fi connection available.

1. Go to the settings app on your smartphone and choose "More".



2. Now choose "Tethering & portable hotspot".

	0.00 K/s 💲 🔌 : 🚰 📋 10:58						
← Wireless & networks							
Airplane mode							
Tethering & portable hotspot							
VPN							
Emergency broadcasts							
NFC							
NFC Allow data exchange when the phone touches another devi							
Android Beam Unavailable because NFC is turned off							
Tap & pay							

- 3. Now connect your smartphone to your windows laptop through USB.
- 4. Enable "USB tethering"

ψ	4.55 K/s 🛠 🔌 🕬 🚺 10:59
Tethering & portable hotspot	
Tethering	
USB tethering Tethered	
Bluetooth tethering Notsharing this phone's Internet connection	•
Portable hotspot	
Portable Wi-Fi hotspot Not sharing this phone's Internet connection via hotspot	
Set up Wi-Fi hotspot nitja WPA2 PSK portable Wi-Fi hotspot	

5. Your smartphone will now show that it's sharing your connection.



6. On the computer. Right click the internet icon and select "Open network & internet settings"



7. In the new windows select "Network and sharing center"



11. On the left side you can pick " Change adapter settings"



12. Now you should see 2 connections. 1 is your connected phone connection (Named Remote NDIS). The other is your cable port. If you have multiple adapters and you are not sure which is your cable port. Insert a cable. The network adapter will change its status and now you know which adapter is your cable port. Unplug the cable after checking.





13. Now select both connections. And right click on your phone connection.

14. Now choose "Bridge connections"

		Ethernet 6				Ethernet 7	
\checkmark		1	Disable		10	Netwerk 28	
	A	Α	Status			Remote NDIS based Int	
			Diagnose				
			Bridge Connections				
			Create Shortcut				
		•	Delete				
		•	Rename				
		•	Properties				

15. Windows now creates the network bridge.





16. When the bridge is created you can connect a LAN cable between the notebook and the CTouch screen. The notebook will now share it's connection to the screen.



Ethernet 6 Network cable unplugg... ASIX AX88179 USB 3.0 t...



Ethernet 7 Enabled, Bridged Netwerkbrug Netwerk 28 Microsoft Network Ada...

17. When you are done using the connection you can delete the bridge to restore normal functioning of the laptop.

